



ERGO SUN

TERRACE PLATFORM





TERRACE PLATFORM



The new ERGO sun platforms from 2M are quick to build and quick to dismantle. They are compact and suitable for almost any subsurface. This makes them the perfect solution for mobile terrace systems and beer gardens.



Leg mount

The 2M leg mount made of die-cast zinc is designed for use with round pipe or square pipe with dimensions of 40 mm to 60 mm.

The leg can be compacted using an M10 adjustment screw or via an eccentric quick release system depending on the customer's wishes – and it is possible to switch between these configurations in seconds.



Surfaces

2M's "ERGO sun" can be covered with Bangkirai (Yellow Balau), Douglas Fir, WPC (wood polymer composite) and many other surfaces and can be tailored exactly to the relevant requirements and preferences.



Adaptability

Thanks to the extensive accessories including rails and stairs, as well as a large selection of plug-in legs, the mobile terrace system can be used on almost every subsurface.





DETAILS







Platform corner with Bankirai surface



Supporting structure when used with decking



TECHNICAL DATA



Product category Terrace platforms

Movable/StationarymovableDimensions2 m x 1 mSpecial size possibleyes

Weight42 kgBacking plate thickness22 mmFrame height90 mm

Pit depth Horizontal test load 1/10 of the vertical test load

Vertical test load 8.5 kN/m² (867 kg/m²)

Horizontal traffic load 1/10 of the vertical traffic load

 $\label{eq:vertical traffic load} Vertical traffic load \qquad \qquad 5.0\,kN/m^2\, \big(510\,kg/m^2\big)$

Max. stage height

TÜV certificate DIN 13814, 4112, 1055, 15921





ACCESSORIES










































































WORKING TOGETHER TO GET THE BEST RESULTS WITH YOUR VISION AND OUR PASSION.

References:

2M-DEUTSCHLAND.DE/EN/REFERENCES

ENQUIRE NOW!



Andre Nölle Sales Manager

- → 02102/13399-13
- → info@2m-deutschland.de



Gerrit Pape Project Manager

- → 02102/13399-14
- → info@2m-deutschland.de